



BLUELINE

THE NEXT STAGE IN LITHIUM

P³ RECOVERY UNIT PORTABLE POWER PACK (P³)

24V, 36V, 48V

The P3 is a **MOBILE, MULTI-VOLTAGE**, lithium-ion battery designed to move industrial equipment. A single operator can unload or load an entire equipment fleet with the power and versatility of the Portable Power Pack.

The P3 is capable of **RESCUING AND MOVING INDUSTRIAL EQUIPMENT** with the operating voltages of 24v, 36v or 48v. It is equipped with interchangeable brackets to allow for secure the P3 to a forklift carriage or LBR, as well as a tow handle and wheels for ease of mobility. The P3 charger consists of a 110VAC input with an output of 25amps. The charger can be operated standalone or mounted.



Includes Wall-Mounted Charger

SOLUTIONS

RESCUE DEAD EQUIPMENT

ELIMINATE LEAD ACID CARTS

UNLOAD NEW FORKLIFTS
(TYPICALLY SHIPPED WITHOUT BATTERIES)

BENEFITS



IMPROVE SAFETY

- Prevent tethering injuries
- Eliminate heavy, lead acid carts
- Avoid lead acid spills



LOWER COSTS

- Prevent equipment damage from tethering
- Lower service technician time
- Decrease lead acid storage
(frees up valuable sq ft)



IMPROVE EFFICIENCY

- Reduce equipment downtime
- Improve service response time
- Convenient tech solution for customer
(No service calls required)

THE NEXT
STAGE IN

LITHIUM

FEATURES

- A STATE-OF-CHARGE INDICATOR**
FOR QUICK VIEWING
- B TELESCOPING HANDLE**
FOR SUITE CASE STYLE TOWING
- C INTERCHANGEABLE MOUNTING BRACKETS**
FOR SECURING TO FORKLIFT CARRIAGE OR LBR
- D WHEELS FOR EASY MOVING**
- E CHARGING PORT**
FOR USE WITH P³ CHARGER
- F MULTI-VOLTAGE COMPATIBLE**
24v 36v 48v
- G SIDE HANDLES**
FOR EASY LIFTING
- H STEEL CASE CONSTRUCTION**
FOR OPTIMAL DURABILITY



OPTIONAL ADD-ONS

P3 EXTENSION CABLE KIT

(1) 8' 4/0 SB175 - SB350 RED | (1) 8' 4/0 SB175 - SB350 GREY | (1) 8' 4/0 SB175 - SB350 BLUE

SPECIFICATIONS

VOLTAGE(S)	24v 36v 48v
CAPACITY	63ah, 50ah USABLE
WEIGHT	95 - 100 lbs
DIMENSIONS	30" x 15" x 8"
OUTPUT CONNECTOR TYPE	SB175 RED (24v), GREY (36v) & BLUE (48v)
MAX CONTINUOUS DISCHARGE	25a CONTINUOUS
MAX PEAK DISCHARGE (30 SEC)	120a
CHARGE TIME	APPROX. 2 HOURS

AC INPUT	120 VAC
DC INPUT	25a
WEIGHT	30 LBS
DIMENSIONS	14.25" x 5.75" x 23.75"
COOLING SYSTEM	FORCED AIR

*DISCLAIMER: THE PORTABLE POWER PACK (P3) IS NOT DESIGNED OR INTENDED TO BE USED AS A COUNTERWEIGHT OR LOAD LIFTING FOR ANY AND ALL MODELS OF FORKLIFTS / INDUSTRIAL EQUIPMENT. THE P3 IS SOLELY DESIGNED FOR FORWARD OR REVERSE TRAVEL AND IS NOT A DIRECT REPLACEMENT BATTERY FOR ANY EQUIPMENT. PLEASE REFER TO THE P3 OPERATING MANUAL OR WARRANTY FOR FURTHER INFORMATION.

READER'S CHOICE • PRODUCTS OF THE YEAR



BLUELINE



608 927 6695



SALES@BLUELINEBATTERY.COM



WWW.BLUELINEBATTERY.COM